

ViewStar series



- On site parameters and control modes adjustable.
- Automatic 12/24V detection
- PWM regulation
- Widely used, automatically recognize day/night
- Clear, readable 3-digit LCD Display and symbols
- Display for panel current, load current, and battery voltage, Ah etc
- Gel, Sealed and Flooded battery type option
- Four push button to select displayed value
- Integrated temperature compensation
- Fully electronically protected
- Fully reverse protection
- Use MOSFET as electronic switch.
- Negative ground
- Large terminals

VS1024N, VS2024N, VS3024N, VS4024N,

VS5024N, VS6024N

VS2048N, VS3048N, VS4048N, VS5048N,

VS6048N

SOLAR SYSTEM CONTROLLER

Rated Current: 10A, 20A, 30A, 40A, 50A, 60A

System Voltage: 12/24V, 12/24/48V



Load work modes:

ON/OFF,

DUSK to DAWN,

DUSK+ dual flexible timer,

REAL TIME CONTROL



Application :

Ideal for off-grid solar system that loads
are normally on or controlled by manual

- ★ Solar home system
- ★ Solar light system
- ★ Solar CCTV system
- ★ Solar traffic system
- ★ Wild automatic detection equipment



Our Advantage :

- ★ Sophisticated R&D has over 20 years research experience's and works in close collaboration with Beihang University.
- ★ Professional technical and service team
- ★ Using world top class electronic components; all the components are industrial grade
- ★ High quality products with reasonable price; the failure rate is less than 2 per1000 pcs
- ★ Practical application in more than 120 countries
- ★ Expected 10 years lifetime
- ★ 2 years warranty

Electrical parameters	
System voltage	12 / 24V,12/24V/48V
Nominal battery current	10A,20A,30A,40A,50A,60A
Charge circuit voltage drop	≤0.24V
Discharge circuit voltage drop	≤0.16V
Self consumption	≤44mA

Model	VS1024N	VS2024N	VS3024N	VS4024N	VS5024N	VS6024N
Rated current	10A	20A	30A	40A	50A	60A
Rated voltage	12V/24V Auto					
Terminals	4mm ²	10mm ²	16mm ²	35mm ²	35mm ²	35mm ²
Net Weight	0.2kg	0.4kg	0.7kg	0.9kg	1.2kg	1.3kg
Working temperature	-35°C - +55°C					

Model	VS2048N	VS3048N	VS4048N	VS5048N	VS6048N
Rated current	20A	30A	40A	50A	60A
Rated voltage	12V/24V/48V				
Terminals	16mm ²	35mm ²	35mm ²	35mm ²	35mm ²
Net Weight	0.7kg	0.9kg	1.2kg	1.3kg	1.4kg
Working temperature	-20°C - +55°C				